

SUPERBIKE - 2025

		RIM	WIDTH	DIAMETER centre	DIAMETER shoulder	WEIGHT	HOT PRESSURE recommended range *minimun prescription (in service)	HOT PRESSURE recommended range *minimun prescription (after warmers)	WARMERS usage
		reccomended inches	mm (inches)	mm (inches)	mm (inches)	kgs (lbs/pound)	bar (psi)	bar (psi)	°C (°F)
D R Y	DIABLO SUPERBIKE								
	front 125/70 R17	3.50	124 (4.88)	610 (24.02)	508 (20.00)	4.3 (9.5)	2.2/2.4 (32/35)	2.2/2.4 (32/35)	40 < > 60 mins. @ 80-90°C (176-194°F)
	rear 200/65 R17	6.00	202 (7.95)	672 (26.45)	530 (20.87)	6.8 (14.9)	1.7*/1.8 (24.6*/26)	1.65*/1.8 (24*/26)	
I N T E R M	DIABLO WET								
	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.2 (9.3)	2.2/2.4 (32/35)	2.2/2.4 (32/35)	70-80°C (158-176°F)
	rear 200/60 R17	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6,8 (14,9)	1.8 (26)	1.7 (24.6)	40-50°C (104 - 122°F)
R A I N	DIABLO RAIN								
	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.2/2.3 (32/33.4)	2.3/2.4 (33.4/35)	20 < > 30 mins. @ 40-50°C (104 - 122°F)
	rear 200/60 R17	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6,8 (14,9)	1.9/2.1 (27.5/30.5)	2.0/2.2 (29/32)	